





Trim Type	Description	Service	Leakage	Trim characteristic
LSV-100™ Top Guided Trim 	Top guided, unbalanced, single seat trim. This style trim is suitable for pressure drops up to 600 psi in a non-cavitating environment. Your most economic choice for standard control applications.	Up to 6" Standard Class 150 Class 300	Class IV	Fast Opening Linear Equal %
LSV-200™ Cage Guided Trim 	Cage guided balanced and unbalanced trim. This is the preferred trim style for modulating control when moderate flow rates exist. The balanced trim is used for sizes over 2" to reduce actuator force requirements.	Up to 6" Standard Class 125/150 Class 250/300 Class 600	Class IV, Class VI Optional	Linear Equal %
MSV-100™ Venturi Ball Design 	Our unique venturi ball design provides superior control, long life and low maintenance costs for moderate pressure drop applications. The MSV-100 is designed for flanged applications. Seat replacement is accomplished on the bench.	Up to 8" Moderate Class 600 Class 900 Class 1500	Class V	Linear
Hi-100* Venturi Ball Design 	This unique venturi ball design provides superior control, long life and low maintenance costs for severe pressure drop applications. The Hi-100 is designed for in-line repair using quick change trim.	Up to 12" Severe All Classes	Class V	Linear

# Warranty

Each DFT® Inc. product is warranted against defects in material and workmanship for a period of one year after being placed in service, but not exceeding 18 months after shipment, when these products are properly installed, maintained and used within the service and temperature and pressure ranges for which they were designed and manufactured, and provided they have not been subject to accident, negligence, alteration, abuse, misuse or the like. This warranty extends to the first purchaser only. All defective material must be returned to the person from whom you purchased the product, transportation prepaid, free of any liens or encumbrances and if found to be defective will be repaired free of charge or replaced, at the warrantor's or DFT's option.

FOR A COMPLETE UNDERSTANDING OF YOUR SOLE AND EXCLUSIVE LEGAL RIGHTS AND REMEDIES, AND THE PROCEDURES TO BE FOLLOWED WITH RESPECT TO ANY CLAIMS, PLEASE REFER TO THE "LIMITATION AND DISCLAIMER OF WARRANTIES AND LIABILITIES," AVAILABLE ON REQUEST FROM DFT. THE EXPRESS WARRANTIES SET FORTH IN THAT DOCUMENT AND THE OBLIGATIONS AND LIABILITIES OF DFT THEREUNDER ARE EXCLUSIVE AND ARE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER OBLIGATIONS AND LIABILITIES OF DFT. IT IS UNDERSTOOD THAT THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION OF THE EXPRESS TERMS IN THE "LIMITATION AND DISCLAIMER OF WARRANTIES AND LIABILITIES." UNDER NO CIRCUMSTANCES SHALL DFT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, ECONOMICAL, DIRECT, INDIRECT, GENERAL OR SPECIAL DAMAGES, EXPENSES OR LOSSES RELATING TO ANY BREACH OF WARRANTIES.

It is expressly understood and agreed that unless a statement is specifically identified in this brochure as a warranty, the statements made herein relating to DFT's products are not express warranties, but are merely for informational, illustrative and identification purposes only.

**DFT**®  
INC.

**REPRESENTED BY**

DFT® and HI-100® are registered trademarks of DFT Inc. LSV-100™ and LSV-200™ are trademarks of DFT Inc. All other trademarks are the properties of their respective owners and are used for purposes of identification only.